

WHAT IS CLAIMED IS:

1. A protective strap for use in spirally winding around a handle, said protective strap comprising:

5 a main body being an elongated strap member having two lateral edges, two end edges, a top side and a bottom side, each of said two lateral edges being longer in length than each of said two end edges; and

 a distinctive strap disposed on said top side of said main body and having two lateral fringes and two end fringes, said two lateral fringes being respectively longer in
10 length than said two end fringes, the width between said two lateral fringes of said distinctive strap being smaller than that between said two lateral edges of said main body, said distinctive strap being parallel to one of said two lateral edges of said main body.

15 2. The protective strap as defined in claim 1, wherein said main body comprises a nonwoven fabric layer and a polyurethane (PU) layer coated on a top surface of said nonwoven layer, said top side of said main body coinciding a top surface of said PU layer.

20 3. The protective strap as defined in claim 1, wherein said bottom side of said main body comprises a first bottom surface and two second bottom surfaces respectively extending from bilateral ledges of said first bottom side to bilateral edges of said top side.

25 4. The protective strap as defined in claim 1, wherein said distinctive strap is an

elongated aluminum strap having a shining surface and is fixedly adhered to said main body.

5 5. The protective strap as defined in claim 1, wherein the width between said two lateral fringes of said distinctive strap is one-fourth of that between said two lateral edges of said main body.

10 6. The protective strap as defined in claim 1, wherein said distinctive strap abuts one of said two lateral edges of said main body at one of said two lateral fringes thereof.

15 7. The protective strap as defined in claim 1, wherein said main body further comprises a recessed portion positioned at a side of said top side and having a width substantially equal to the width of said distinctive strap; said distinctive strap is adhered to said recessed portion such that a top surface of said distinctive strap is flush with or lower than said top side of said main body in elevation.

20 8. The protective strap as defined in claim 1, wherein said distinctive strap has a thickness of no more than 0.1 mm.

 9. The protective strap as defined in claim 1, wherein said distinctive strap has a thickness of 0.05 mm.

25 10. The protective strap as defined in claim 1, wherein one of said two lateral edges of said main body is at a distance of less than 3 mm from one of said two lateral

fringes of said distinctive strap after said protective strap is completely wound around the handle.

11. The protective strap as defined in claim 1, wherein said main body further
5 comprises two recessed portions positioned respectively at bilateral sides of said top side thereof, and each of said two recessed portions is less in width than said distinctive strap, such that said distinctive strap is adhered to one of said recessed portions and a part of said top side to form a stepped portion on said distinctive strap.

10 12. The protective strap as defined in claim 1, wherein said distinctive strap is directly printed on said top side of said main body.

13. The protective strap as defined in claim 1, wherein said distinctive strap is
15 directly paint-coated on said top side of said main body.

14. The protective strap as defined in claim 1, wherein said main body
comprises a recessed portion in proximity of one lateral edge of said top side thereof;
said distinctive strap is adhered to said recessed portion and is at a distance from said
one lateral edge of said main body.

20